


Features:

- ▣ Support AHD - TVI - CVI - IPC - Analog HD / 960H
- ▣ HDMI/VGA simultaneous video output;
- ▣ 2U Case, 2 SATA (Up to 6TB);
- ▣ 1*10/100Mbps auto-sensing Ethernet port, RJ45 port ;
- ▣ Automatic networking support, a key to add equipment;
- ▣ Cloud services, P2P, alarm information push to phone;
- Support remote access, support RTSP;
- ▣ Mobile phone remote monitoring (iOS, Android);
- ▣ Multi browser access (IE, Chrome, Firefox, Safari);
- ▣ Perfect protection circuit, unique triple watchdog function;
- Support WEB, CMS, Cloudsee Platform;

Model		TRI-VHR532
Video	Codec	SMART H.264+
	Encode	32*4M-N @8fps : 32*1080P @18fps (5 in 1)
	Decode	32*4M-N @8fps : 32*1080P @18fps (5 in 1)
	Multi-mode	Analog:32*4M-N
		Hybird: 16*4M-N + 16*2M(IP)
		IP:32*2M(IP)
Audio	Playback	8ch
	Compression	G.711a
	Intercom	Support
Management	Record mode	Manual>Alarm>Motion detection>Timing
	Inquire mode	Inquire by Time/Calendar/Event/Channel
	Storage Mode	HDD Storage
	Backup	USB, SATA
Interface	Interface	32*BNC(Support Coaxitron)
	HDMI output	1*HDMI
	VGA output	1*VGA
	Audio I/O	8in, 1out
	Alarm I/O	Optional
	Ethernet port	1*10/100Mbps Ethernet port, RJ45 port
	PTZ contorl	1*RS485, Support for multiple PTZ protocol
	USB port	2*USB2.0 ports
	HDD	2*SATA interface (Up to 6TB)
General	Temperature	0°C- + 55°C
	Humidity	10% -90% RH
	Power supply	12V/4A
	Consumption	<10W(Without HDD)